



Universal White Primer

1S111

4411008

A waterborne high performance modified acrylic primer suitable for many surfaces including wood, metal, high density urethane (HDU), properly prepared brick, block and concrete. Excellent adhesion qualities, fast drying and easy to sand.



Features & Benefits

- Excellent adhesion
- Fast drying
- Easy to sand

Compatible Surfaces

Wood, metal, high density urethane (HDU), properly prepared brick, block and concrete surfaces

Directions For Use



Surface Preparation:

- Wood: clean thoroughly, lightly abrade and tack surface prior to application
- Metal: clean with fast evaporating pre-paint wax and grease remover, lightly abrade and re-clean
- Brick, block or concrete: clean thoroughly and remove all loose mortar.
Surface must be completely dry before painting.



Matthews Paint • Toll Free: 800.323.6593 • Fax: 800.947.0377
www.matthewspaint.com • www.1shot.com
760 Pittsburgh Drive • Delaware, OH 43015

Product Information Effective 01/17
Part No. 1S111 01/17
© 2017 Matthews Paint Company

Directions For Use (Continued)



Mix Ratio:

For spray applications, reduce by no more than 15% with distilled water.



Application:

- Apply with brush or roller
- Apply: 1 wet coat
 - Flash 30 minutes
 - Apply a second wet coat



Drying Times:

- Dry to handle: 45 minutes
- Dry to topcoat: 3 hours

Do not apply at temperatures below 55°F (13°C)

Technical Data:

VOC.....	2.34 lbs. per gallon or 280.43 grams per liter
Solids by Weight.....	39.54
Solids by Volume.....	25.41
Theoretical Coverage.....	407 square feet per gallon at 1 mil 100% transfer

Precautions:

Prevent from freezing.

Important:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

Emergency Medical or Spill Control Information:

US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.