



Speed Prep Cleaner

45330SP/01

Proper substrate preparation plays an important role for the success of a paint job. Surface contamination is the most common reason for premature coating failures.

Speed Prep Cleaner has been specifically designed to remove waxes, grease, silicones, and other contaminants from bare or coated metals and therefore eliminate avoidable adhesion problems.



Features:

Packaged ready for use.....No mixing; consistent results
Solvent borne.....Excellent for removing wax, grease and oil contamination

Benefits:

Directions for Use

45330SP/01 Speed Prep:



- Apply a generous amount of 45330SP/01 on the surface with a clean cloth or a hand held spray bottle and wipe the surface.
- The initial application will float contaminants to the surface, and the second wipe using a separate clean dry cloth, will remove contaminants.
- For maximum results, wipe the surface dry while it is still wet, using a clean white cloth in one direction. This will eliminate the smearing of contaminants. Be sure to change rags frequently.
- Never let the cleaner dry on the surface.
- Use 45330SP/01 before and after sanding.

Caution: Do not use this product on fiberglass or plastic parts. Application on these surfaces can generate static build-up, which can result in a flash fire. Do not use on fresh/uncured finishes, otherwise softening of coating may occur.

Technical Data:

Color	Clear
VOC lbs./US gal.	6.37 VOC

45330SP/01

Speed Prep Cleaner

Important: Refer to SDS for safety guidelines. Use in a well ventilated area with appropriate Personal Protective Equipment (PPE) to protect eyes, skin, and respiratory system.

See Safety Data Sheet and Labels for additional safety information and handling instructions.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION - US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400
Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.



The World's Finest Coating For Architectural Signage

760 Pittsburgh Drive
Delaware, OH 43015
Toll Free: 800/323-6593
Toll Free FAX: 800/947-0377