



Splash

1S123

4704700

Splash is formulated as an application fluid concentrate, designed to aid in the application of pressure sensitive vinyl films and graphics. It allows for repositioning and removal of trapped air, by acting as a buffer between the film adhesive and the surface until it is squeegeed out from beneath the film or graphic.



Directions for Use

- Combine the contents (8 fluid ounces) of one container of Splash with 120 ounces of water in clean mixing vessel and stir slowly and thoroughly.
- Move this mixture into an atomizing spray bottle for use.
- Spray Splash onto the adhesive side of pressure sensitive vinyl films and/or onto the clean surface to which they will be applied.
- Do not use on films or applications in which the film manufacturer specifies a “dry” application.
- Use a vinyl graphics application squeegee to remove fluid and trapped air from beneath the film prior to removing the application tape.
- On larger graphics, applying Splash to the surface of the application tape itself, post application, can aid in tape removal.
- Use a clean, dry cloth to remove excess Splash from the area after removing application tape.
- Prevent from freezing.



Matthews Paint • Toll Free: 800.323.6593 • Fax: 800.947.0377
www.matthewspaint.com • www.1shot.com
760 Pittsburgh Drive • Delaware, OH 43015

Product Information Effective 06/16
Part No. 1S123 06/16
© 2016 Matthews Paint Company

Important:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

Emergency Medical or Spill Control Information:

US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.