



## 4005AA

1 Shot Speed Dry UV Acrylic Clear is a fast drying UV resistant clear top-coat that prevents colors from fading and provides mild abrasion resistance. Intended for use on interior or exterior printed PVC vinyls and for solvent, eco-sol, UV and thermal resin prints.



### Features & Benefits

- Dries to touch in 30 minutes
- UV resistant

### Compatible Surfaces

Printed PVC vinyls and solvent, eco-sol, UV and thermal resin prints.

### Directions For Use



#### Surface Preparation:

Tack printed surface free of dust after allowing sufficient, thorough drying time. Usually no less than 12 hours.



#### Application:

Before applying, shake aerosol can vigorously for one minute often during use. Hold the aerosol can upright 10-12" from surface and spray in a steady back and forth motion, slightly overlapping each stroke. Keep the aerosol can moving while spraying to avoid sagging.



## Directions For Use (Continued)

---



### Drying Times:

- Dry to touch: 30 minutes
- Dry to handle: 1 hour

Dry times are at 70° F (20° C) and 50% relative humidity.

### Technical Data:

|                           |  |
|---------------------------|--|
| VOC .....                 | 4.69 lbs/gallon                        |
| Solids by Weight .....    | 12.50                                  |
| Solids by Volume.....     | 8.89                                   |
| Theoretical Coverage..... | 142 square feet at 1 mil 100% transfer |

### Limitations:

- Do not expose to heat or store at temperatures above 120° F (50° C).
- Use with adequate ventilation.
- Avoid spraying in very windy, dusty conditions.
- Extreme heat and certain solvents can cause softening of the clear, so testing for cleaning and exposure is recommended.

### Important:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

**See Material Safety Data Sheet and Labels for additional safety information and handling instructions.**

### Emergency Medical or Spill Control Information:

US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.