



High Build White Primer

1S109

4411010

A high viscosity, waterborne primer with excellent filling and building characteristics. Ideally suited for HDU (High Density Urethane), most woods and foams. Exhibits high coverage and opacity characteristics and can be easily sanded smooth.



Features & Benefits

- Mildew resistant
- Excellent filling

Compatible Surfaces

HDU (High Density Urethane), most wood and foams.

Directions For Use



Surface Preparation:

Apply to dry surfaces free of chemical and physical debris.

Reducers:

If absolutely necessary for spray application, reduce with no more than 10% water.



Application:

Apply with synthetic brush, roller or spray.



Matthews Paint • Toll Free: 800.323.6593 • Fax: 800.947.0377
www.matthewspaint.com • www.1shot.com
760 Pittsburgh Drive • Delaware, OH 43015

Product Information Effective 01/17
Part No. 1S109 01/17
© 2017 Matthews Paint Company

Directions For Use (Continued)



Drying Times:

- Allow 45 minutes between coats
- Dry to topcoat: 8-12 hours or overnight

Compatible Topcoats:

Oil and Waterborne products

Equipment Cleaning:

Clean equipment and hands with warm, soapy water

Technical Data:

VOC.....	1.99 pounds per gallon or 238.48 grams per liter
Solids by Weight.....	43.95
Solids by Volume.....	27.83
Theoretical Coverage.....	446 square feet @ 1 mil 100% transfer

Important:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

Emergency Medical or Spill Control Information:

US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.